

MEGAMC® 2065

20" OD - 65" OD (500MM - 1600MM)



MADE FOR

UNDERGROUND
CONSTRUCTION



ABOUT MEGAMC

The McElroy MegaMc® fusion machines are a revolutionary mix of muscle and versatility. They were the first large-diameter machines that brought the flexibility of the small-diameter machines to large-diameter fusion. Rugged and tough, they are designed to meet the demands of jobsites worldwide and are equally capable of performing quality fusions in the ditch and in close quarters.

The MegaMc carriages are mounted on a wheeled chassis for portability and convenience on large-diameter pipeline jobsites. Easily towable to the fusion area, they remain stationary as sticks of pipe are fused and pulled through.

All of the fusion functions on the MegaMcs are powered smoothly by hydraulics including the clamping and unclamping of the jaws and the fast and efficient facing of the pipe ends. Hydraulic pipe lifts aid in loading and unloading pipe from the machine.

The MegaMcs are compatible with the McElroy DataLogger®, which records and documents the entire fusion process. Joint records are used to verify that proper fusion procedures have been followed prior to installation and can be stored and analyzed in the Vault™, a secure server on the internet.

Pipe type, job requirements and fusion standards are all important aspects of planning a fusion job. The MegaMcs are available in a variety of cylinder forces to meet your jobsite needs.

MEGAMC 2065 SERIES 2

Made for the largest of pipe applications, the MegaMc 2065 has been used around the world as large-diameter polyethylene pipeline projects grow in every industry. It will butt fuse pipe from 20" OD to 65" OD (500mm to 1600mm) and allows for fusions of most fittings without special holders or removal of the outer jaws. Equipped with a unique semi-automatic control system, only one operator is required. The facer and heater hydraulically index left to right and can pivot in and out of the fusion machine. Mitered inserts are also available for fabricating ells.

ADDITIONAL IMAGES



STANDARD FEATURES

- ✓ Patented Centerline Guidance System for equal distribution of force around the joint
- ✓ Industry standard semi-automatic hydraulic control system
- ✓ Simple-to-use independent jaw control puts more flexibility in the hands of the operator
- ✓ Advanced digital heater control offers better temperature control
- ✓ Rugged outriggers for added stability
- ✓ Dual hydraulic pipe lifts aid in loading and unloading pipe
- ✓ Standard Hydraulic Clamping
- ✓ Serrated jaws and inserts keep pipe from slipping during fusion
- ✓ DataLogger® compatible
- ✓ Advanced blade design for smooth face and long life
- ✓ ISO-compliant industrial Teflon-coated heater plates
- ✓ Hard-anodized aluminum wear surfaces for corrosion resistance



DataLogger
COMPATIBLE

MEGAMC[®] 2065

20" OD - 65" OD (500MM - 1600MM)

SPECIFICATIONS

MODELS		ENGINE		MOBILITY	
A6300102	High Cylinder Force, 240V	Engine Horse Power	10 HP	Mobility Type	Tires - 12 - 16.5LTF, F-12
A6300104	High Cylinder Force, 415V			Transportation	Pulled via towing ring
WEIGHTS		POWER		Lifting	Lift points and lifting assembly
Machine	14,000 lbs. (6,350.3 Kg)	MegaMc [®] 2065 Output Power	49.6 kVA	MACHINE DIMENSIONS	
Spreader Bar	650 lbs. (294.8 Kg)	MegaMc [®] 2065 Output Power	50 kVA	Machine Length	186.5" (4,737.1mm)
20" - 48" Heater Heater	600 lbs. (272.2 Kg)	Plug type	125A, 4 Pole, 5 Wire	Machine Width	108" (2,743.2mm)
48" - 65" Heater Heater	713.5 lbs. (323.6 Kg)	Plug type	200A, 4 Pole, 4 Wire	Machine Height	112" (2,844.8mm)
Facer	1,200 lbs. (544.3 Kg)	Facer	Hydraulic	INCLUDES	
Shipping Weight	14,400 lbs. (6,531.7 Kg)	CHASSIS		Fusion machine, facer, 48" and 65" heaters, 63.51" Master insert set, and lifting assembly.	
HYDRAULICS		Frame	Welded steel construction		
System Pressure	1,500 PSI (103.4 BAR)	Brake	Mechanical		
Fusion Pressure	1,500 PSI (103.4 BAR)				
Hydraulic Reservoir Capacity	24 Gallons (90.8 Liters)				